



specifications compliant with SFF
8472 digital diagnostic monitoring
interface for optical transceivers

- ✧ Power Supply +3.3V
- ✧ Operating case temperature Range:
Commercial: 0~ 70°C
Extended: -20~ 85°C
Industrial: -40~ 85°C
- ✧ RoHS compliant

Features:

- ✧ UP to 25.78Gb/s bit rates
- ✧ Hot-Pluggable SFP28 footprint
- ✧ Duplex LC connector
- ✧ CWDM DFB laser transmitter
- ✧ Up to 15km on 9/125m SMF
- ✧ 2-wire interface for management

Applications:

- ✧ 25GE Ethernet
- ✧ eCPRI&CPRI

Part Number Ordering Information

OP3015D-xx	25GE, SFP28 LR 15km CWDM 1271~1371nm optical transceiver, 0~70°C, xx:27,29,31,33,35,37
OP3015DE-xx	25GE, SFP28 LR 15km CWDM 1271~1371nm optical transceiver, -20~85°C, xx:27,29,31,33,35,37
OP3015DI-xx	25GE, SFP28 LR 15km CWDM 1271~1371nm optical transceiver, -40~85°C, xx:27,29,31,33,35,37

Description:

OPWAY's OP3015Dx-xx SFP28 transceivers are designed for use in Ethernet links up to 25.78 Gb/s data rate and up to 15 km link length. They are compliant SFF-8472 , and compatible with SFF-8432 and applicable portions of SFF-8431. The product is RoHS compliant and lead-free per Directive 2011/96/EU.

● Absolute Maximum Ratings

Parameter	Symbol	Min.	Typical	Max.	Unit	Note
Storage Temperature	T _S	-40		+85	°C	
Case Operating Temperature	T _c	0		+70	°C	Commercial
Case Operating Temperature	T _c	-20		+85	°C	Extended
Case Operating Temperature	T _c	-40		+85	°C	Industrial
Maximum Supply Voltage	V _{cc}	0		3.6	V	
Relative Humidity(Non-condensing)	RH	0		85	%	

● Electrical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit	Note
Supply Voltage	V _{cc}	3.135		3.465	V	
Supply Current	I _{cc}			450	mA	Commercial
Supply Current	I _{cc}			550	mA	Extended
Supply Current	I _{cc}			600	mA	Industrial
Power Consumption	P			1.5	W	Industrial
Power Consumption	P			1.8	W	Extended
Power Consumption	P			2.0	W	Industrial
Data Rate	R	-	25.8		Gb/s	
Fiber Length	L			15	KM	
Transmitter Section:						
Input differential impedance	R _{in}		100		Ω	1
Differential input voltage swing	V _{in,pp}	180		450	mV	2
Transmit Disable Voltage	V _D	2		V _{cc}	V	3
Transmit Enable Voltage	V _{EN}	V _{ee}		V _{ee} +0.8	V	
Receiver Section:						
Single Ended Output Voltage Tolerance	V	-0.3		4	V	
Rx Output Diff Voltage	V _O	180		450	mV	
LOS Fault	V _{LOS fault}	2		V _{cc}	V	4
LOS Normal	V _{LOS norm}	V _{ee}		V _{ee} +0.8	V	4

Note:

1. Connected directly to TX data input pins. AC coupling from pins into laser driver IC.
2. Per SFF-8431 Rev 3.0
3. Into 100 ohms differential termination.
4. LOS is an open collector output. Should be pulled up with 4.7k – 10kΩ on the host board. Normal operation is logic 0; loss of signal is logic 1. Maximum pull-up voltage is 5.5V.

● Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit	Note
Transmitter Section:						
Center Wavelength	λ _t	λ -6.5	λ	λ +6.5	nm	
spectral width(-20dB)	Δλ			1	nm	
Average Optical Power	P _{avg}	0		7	dBm	27,29,31
Average Optical Power	P _{avg}	2		8	dBm	33,35,37
Laser Off Power	P _{off}			-30	dBm	
Side Mode Suppression Ratio		30				
Extinction Ratio	ER	4.0			dB	
Optical Return Loss Tolerance				-12	dB	

Receiver Section:						
Center Wavelength	λ_r	1260		1380	nm	
Receiver Sensitivity(Ave)	Sen			-19.0	dBm	1
Receiver Sensitivity(OMA)	Sen			-19.6	dBm	1
Los Assert	LOS _A	-35		-	dBm	
Los Dessert	LOS _D			-20	dBm	
Los Hysteresis	LOS _H	0.5			dB	
Overload		-7			dBm	

Note:

1. Measured with a PRBS 2³¹-1 test pattern, @25.78Gb/s, BER<5E-5.

● Timing Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
TX_Disable Assert Time	t_off			100	us
TX_Disable Negate Time	t_on			2	ms
Time to Initialize 2-wire interface	t_2w_start_up			300	ms
Time to Initialize	t_start_up			300	ms
Time to Initialize cooled module and time to power up a cooled module to Power level II	t_start_up_cooled			90	s
Time to Power Up to Level II	t_power_level2			300	ms
Time to Power Down from Level II	t_power_down			300	ms
Tx_Fault assert	Tx_Fault_on			1	ms
Tx_Fault assert for cooled module	Tx_Fault_on_cooled			50	ms
TX_FAULT Reset	t_reset	10			us
Rx_LOS assert delay	t_los_on			100	us
Rx_LOS negate delay	t_los_off			100	us

● Pin Function Definition

PIN #	Name	Function	Notes
1	VeeT	Module transmitter ground	1
2	Fault	Module transmitter Fault	2
3	Disable	Transmitter Disable; Turns off transmitter laser output	3
4	SDL	2 wire serial interface data input/output (SDA)	4
5	SCL	2 wire serial interface clock input (SCL)	4
6	MOD-ABS	Module Absent, connect to VeeR or VeeT in the module	2
7	RS0	Rate select0: module inputs and are pulled low to VeeT with > 30 kΩ resistors in the module.	
8	LOS	Receiver Loss of Signal Indication	
9	RS1	Rate select1: module inputs and are pulled low to VeeT with > 30 kΩ resistors in the module.	
10	VeeR	Module receiver ground	1
11	VeeR	Module receiver ground	1
12	RD-	Receiver inverted data out put	
13	RD+	Receiver non-inverted data out put	
14	VeeR	Module receiver ground	1
15	VccR	Module receiver 3.3V supply	
16	VccT	Module transmitter 3.3V supply	
17	VeeT	Module transmitter ground	1

Shenzhen Opway Communication Co., Ltd.

18	TD+	Transmitter non-inverted data output	
19	TD-	Transmitter inverted data output	
20	VeeT	Module transmitter ground	1

Note:

1. The module ground pins shall be isolated from the module case.
2. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.
3. This pin shall be pulled up with 4.7K-10Kohms to VccT in the module.
4. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.





Diagram of Host Board Connector Block Pin Numbers and Names



● Digital Diagnostic Specifications

Parameter	Symbol	Units	Min	Max	Accuracy
Transceiver Temperature	Temp	°C	-40	+85	±5°C
Transceiver Supply Voltage	Voltage	V	3.135	3.465	±3%
Transmitter Bias Current	Bias	mA	0	35	±10%
Transmitter Output Power	Tx-Power	dBm	0	+8	±3dB
Receiver Average Optical Input Power	Rx-Power	dBm	-19	-7	±3dB

● **Transceiver Block Diagram**




● **Recommended Circuit**



Recommended High-speed Interface Circuit

● **Mechanical Dimensions**



Published by Shenzhen OPWAY Communication Co., Ltd.
Copyright © OPWAY
All Rights Reserved